


50 ohms 2 way Power Divider SMA Connectors From 0.5GHz to 18GHz Rated at 30 Watts

Technology Specifications Rev:A0

P03-250718



Power Divider

- ◆ 2-Way Power Divider
- ◆ Wilkinson Design
- ◆ Wide Frequency Range
- ◆ Excellent Reliability
- ◆ Customization available

The HPD0.5-18G-2S is a 2 way Wilkinson power divider that operates from 0.5 to 18 GHz and can handle up to 30 Watts . This power divider offers 17 dB Isolation and 1.50:1 max VSWR. The package interface uses SMA connectors on all of the ports.

The electrical specifications apply for at TA=+25°C in a 50Ω system.

Electrical Specifications				
Parameter	Units	Min.	Typ.	Max.
Frequency Range:	GHz	0.5		18
Nominal Splitter Loss ¹ :	dB		3.0	
Excess Insertion Loss ² :	dB		0.8	1.0
Input VSWR:	/		1.4:1	1.5:1
Output VSWR:	/		1.3:1	1.4:1
Isolation:	dB	17	18	
Amplitude Balance:	dB		±0.3	±0.4
Phase Balance:	Deg		±3.0	±4.0
Forward Power	W cw			30
Reverse Power	W cw			2

Note:

[1] Nominal Splitter Loss based on splitter factor.

[2] Excess Insertion Loss = (Input Port to Output Port Insertion Loss) – Nominal Splitter Loss.

50 ohms 2 way Power Divider SMA Connectors From 0.5GHz to 18GHz Rated at 30 Watts

Technology Specifications Rev:A0


P03-250718

Mechanical Specifications	
Input and Output Connectors:	SMA-Female(50Ω)
Coupling Connector:	SMA-Female(50Ω)
Dimensions(mm):	150*26*10
ROHS:	Yes
Material:	Aluminum
Weight(Kg):	TBD
Surface Finish:	Black Paint
Environmental Specification	
Operating Temp.	-40°C to +70°C
Storage Temp.	-55°C to +85°C
Environment Class:	TBD
Altitude:	60,000 ft. 1.0psi min (Hermetically Sealed Un-controlled environment)(Optional)
Humidity:	95%RH at 40°C
Shock:	20G for 11msec half sine wave,3 axis both directions

Outline Drawing:

All Dimensions in mm (inches)

Outline Tolerances $\pm 0.3(0.012)$



Test Plots
