


50 ohms 2 way Power Divider 2.92 Connectors From 0.3GHz to 40GHz Rated at 30 Watts

Technology Specifications Rev:A0

P06-250718



Power Divider

- ◆ 2-Way Power Divider
- ◆ Wilkinson Design
- ◆ Wide Frequency Range
- ◆ Excellent Reliability
- ◆ Customization available

The HPD0.3-40G-2K is a 2 way Wilkinson power divider that operates from 0.3 to 40 GHz and can handle up to 30 Watts . This power divider offers 15 dB Isolation and 1.60:1 max VSWR. The package interface uses 2.92 connectors on all of the ports.

The electrical specifications apply for at TA=+25°C in a 50Ω system.

Electrical Specifications				
Parameter	Units	Min.	Typ.	Max.
Frequency Range:	GHz	0.3		40
Nominal Splitter Loss ¹ :	dB		3.0	
Excess Insertion Loss ² :	dB		3.0	3.5
Input VSWR:	/		1.5:1	1.6:1
Output VSWR:	/		1.5:1	1.6:1
Isolation:	dB	15	18	
Amplitude Balance:	dB		±0.4	±0.5
Phase Balance:	Deg		±5.0	±6.0
Forward Power	W cw			30
Reverse Power	W cw			2

Note:

[1] Nominal Splitter Loss based on splitter factor.

[2] Excess Insertion Loss = (Input Port to Output Port Insertion Loss) – Nominal Splitter Loss.

50 ohms 2 way Power Divider 2.92 Connectors From 0.3GHz to 40GHz Rated at 30 Watts

Technology Specifications Rev:A0


P06-250718

Mechanical Specifications	
Input and Output Connectors:	2.92-Female(50Ω)
Coupling Connector:	2.92-Female(50Ω)
Dimensions(mm):	245*26*10
ROHS:	Yes
Material:	Aluminum
Weight(Kg):	TBD
Surface Finish:	Black Paint
Environmental Specification	
Operating Temp.	-40°C to +70°C
Storage Temp.	-55°C to +85°C
Environment Class:	TBD
Altitude:	60,000 ft. 1.0psi min (Hermetically Sealed Un-controlled environment)(Optional)
Humidity:	95%RH at 40°C
Shock:	20G for 11msec half sine wave,3 axis both directions

Outline Drawing:

All Dimensions in mm (inches)

Outline Tolerances $\pm 0.3(0.012)$



50 ohms 2 way Power Divider 2.92 Connectors From 0.3GHz to 40GHz Rated at 30 Watts

Technology Specifications Rev:A0

P06-250718

Test Plots

